

The Industry's Most Flexible, High Performance, and Intelligent Regenerative Series

Innovate the way you test, increase productivity, and reduce test schedules with Pacific Power Source's safe, flexible, scalable, and sustainable solutions.

Our regenerative series offer best in class performance, intelligence, and ease of use. These four-quadrant, multifunctional devices offer integrated AC & DC test capabilities and load options that can eliminate external equipment and simplify your test setup. Put your trust in the best solutions from the market leader.

Choose from two product families for each product category depending on your test requirements. Select based on power levels, voltage ranges, power density, and need for PHIL.

- All-in1 Regenerative AC/DC Power Source AGX or AZX Series
- Regenerative Grid Simulators
 RGS or GSZ Series
- Regenerative Electronic Loads
 RLS or ELZ Series



Regenerative Power > 90%

Greater than 90% energy efficiency. Source and sink to emulate bidirectional power. Robust SiC technology, dynamic and efficient.



Constant Power, Extra Current

Seamless testing over a wide voltage range without power interruption. Extra current at lower voltage. Test a wide range of products.



Wide Frequency Range

Output frequency range from 15Hz to 1000Hz (std) or 3000Hz (option) provides flexibility to address different applications.



Modular and Scalable Power

Modular power up provides future-proofing. Upgrade modules later if needed.



30kVA to 440kVA















Ultra Flexible Output Configuration

Simultaneous AC and DC operation per phase AND automatic switching of output modes provides extensive flexibility.



Programming Capability

Multiple control options, intuitive user interface, powerful waveform tools, and simplified set-up saves time.




Smart Design & Safety

Built-in galvanic isolation and protection limits. Continuous self-calibration. Compact and mobile-friendly cabinets.





SmartSource Suite Control

Embedded web browser based remote control platform to easily create, modify, and run test programs.











6 to 252kVA / kW up to 21kVA / kW in 4U Chassis Parallel up to 168kVA/kW per cabinet

Dual cabinets up to 252kVA/kW

Constant Power Voltage Range:

350Vac L-N/606Vac L-L or ±500Vdc

Single, Split, and Three-Phase






AGX Series High Power Density All-in-1 AC & DC Power Source, Current Source, Load

This 'All-in-One' 4-quadrant test solution can address a wide range of applications and markets. It can serve as a fully programmable AC/DC power source, current source, and load.

- High Frequency:15-1200Hz; Extended Range 1-3000Hz
- · AC, DC, AC+DC
- · Current Source Mode
- Inter-harmonics & Load Options

AC Voltage Source AC DC Current Power Source Supply All-in-1 **AGX** Series DC DC Current Load Source AC Load

All-in-1 AZX Series



RGS Series 2-in-1 Grid Simulator & Load


Designed for the testing and verification of all grid-tied applications. Test to regulatory compliance standards such as IEEE 1547, UL 1741, IEC 61000-3, IEC 61000-4, and more.

- Power level starts at 12kW
- 15-200Hz
- · AC, DC (AC+DC Option)
- · Inter-harmonics included
- Load Option

RLS Series AC & DC Electronic Load

High power 4-quadrant load capability to simulate any linear or non-linear loads. Several AC and DC emulation modes include Constant Current (CC), Constant Resistance (CR), Constant Power (CP).

- 15-1200Hz
- AC, DC
- Inter-harmonics Option











30 to 440kVA / kW

30, 45, 55kVA/kW per cabinet Parallel up to 440kVA/kW

Constant Power Dual Voltage Range:


0~225Vac L-N/0~390Vac L-L and 0~335Vdc 0~440Vac L-N/0~760Vac L-L and 0~650Vdc

Single, Split, and Three-Phase

AZX Series All-in-1 AC & DC Power Source. Current Source, Load, + PHIL

This 'All-in-One' 4-quadrant test solution can address a wide range of applications and markets. It can serve as a fully programmable AC/DC power source, current source, load, and PHIL amplifier.

- High Frequency: 15-1000Hz; Extended Range 1-3000Hz
- · AC, DC, AC+DC
- · Current Source Mode
- · Inter-harmonics Option, Load Option
- · Optimized for PHIL



All-in-1 AZX Series

Work Station

PHIL Simulation Workflow


GSZ Series 2-in-1 Grid Simulator & Load

Designed for the testing and verification of all grid-tied applications. Test to regulatory compliance standards such as IEEE 1547, UL 1741, IEC 61000-3, IEC 61000-4, and more.

- 15-200Hz
- AC, DC (AC+DC Option)
- · Inter-harmonics included
- · Optimized for PHIL; Load Option

ELZ Series AC & DC Electronic Load

High power 4-quadrant load capability to simulate any linear or non-linear loads. Several AC and DC emulation modes include Constant Current (CC), Constant Resistance (CR), Constant Power (CP) AND Circuit Emulation (CE).



- · AC, DC
- · Inter-harmonics Option
- · Optimized for PHIL
- Includes Circuit Emulation Mode





ELZ 4 Quadrant Load includes CE Mode


This mode allows simulation of a wide range of Linear and Non-Linear Electrical Circuit Topologies.



Powerful Programming & Measurement Capability







- · Precise Output Voltage and Load Regulation
- Metering of Volts, RMS Current, Peak Current, Apparent Power & True Power on All Phases
- · Harmonic Measurements
- Built-in Scope and Digitizer


- Phase Angle, Output Transient Programming
- · Sine, Square, Triangle, Clipped Sine,
- Over 200+ User-Defined Arbitrary Waveforms
- · Programmable Output Impedance
- Pre-written test standard sequence options

Ultimate Flexibility with 6 Phase Configurations

Capability to operate in each phase as a different function: voltage source, current source, or load (option).

Multiple Output Modes (Input for Loads)

- FORM1 Single Phase
- FORM2 Split Phase
- FORM3 Three Phase
- FORM4 Two Independent Outputs
- FORM5 Three Independent Outputs
- FORM6 Split Phase + Single Phase Outputs



Multiple Control Options

Easily control and operate our power units with intuitive, user-friendly control options.

- · Touch-Screen Visual Panel
- Intuitive Menu and Soft-keys
- · Shuttle Knob, Numeric Entry Pad
- LAN, GPIB, RS232 & USB Interfaces, CAN/CAN FD/ModBus, Analog Control
- SmartSource Suite Embedded Web Server for Both LAN and USB Interface



SmartSource Suite on any web browser

Unit Dimensions: H x W x D

AGX / RGS / RLS Series: 7.0" x 17.0" x 25.0" / 178 x 432 x 635 mm AZX / GSZ / ELZ Series : 59.8" x 24.0" x 31.9" 1520 x 610 x 810 mm

Founded in 1971, Pacific Power Source is an industry leading manufacturer of AC and DC power test solutions.



